MBV15 Stainless Steel Center Block Pump

Stainless Steel Center Block Pump





MBV15 Stainless Steel Center Block Pump

Stainless Steel Center Block Pump

Emoclew America is the best MBV15 Stainless Steel Center Block Pump manufacturer in USA. Offering quality product to global customers.



Description

Features

- 1/2 in (12.7 mm) center- and end-porting
- No seals to leak or fail
- Quiet running less than 85 dB with easy-to-use remote muffler capability for even lower noise levels
- High flow rates in a small, portable package
- External controller for optional remote operation

Typical Applications

- Machine lubrication servicing
- Cleaning fluids and detergents
- Plating and dip tanks
- Water treatment


Typical Fluids Handled

- Oil
- Water
- Most solvents

Parameter Table

MBV15 Stainless Steel Center Block Pump - Technical Specifications	
Max Working Pressure	100psi(0.7Mpa ,7bar)
Max Flow Rate	15gpm(57lpm)
Max Reciprocating Speed	400cpm
Max Suction Height (Dry Sucking)	4.5m
Max Permitted Grain	3/32in.(2.5mm)
Max.Air Consumption	20gpm(10L/s)
Air Inlet size	1/4in.npt(f)
Air Outlet size	3/8in.npt(f)
Fluid Inlet size	1/2 in.npt(f)or bspt(f)
Fluid Outlet size	1/2 in.npt(f)or bspt(f)
Weight	Aluminum pump 4.5kg; Stainless Steel 6.8kg

Diagram



Installation

