MBV20 PP Plastic Cente Block Pump







Diaphragm Pump

MBV20 PP Plastic Cente Block Pump

Plastic Center Block Pump

As the best China MBV20 PP Plastic Cente Block Pump supplier, Emoclew America provides quality MBV20 PP Plastic Cente Block Pump to global clients.

Description

Features

- 3/4 in (19.05 mm) center- and end-porting
- No seals to leak or fail
- Quiet running less than 85 dB with easy-to-use remote muffler capability for even lower noise levels
- High flow rates in a small, portable package
- External controller for optional remote operation



Typical Applications

- Machine lubrication servicing
- Drum evacuation
- Plating and dip tanks
- Water treatment


Typical Fluids Handled

- Cleaning fluids and detergents
- Chemicals
- Ceramic glazes
- Inks
- Solvents and flammables
- Acids and bases


Parameter Table

MBV20 PP Plastic Cente Block Pump - Technical Specifications	
Max Working Pressure	100psi(0.7Mpa ,7bar)
Max Flow Rate	15gpm(57lpm)
Max Reciprocating Speed	400cpm
Max Suction Height (Dry Sucking)	4.5m
Max Permitted Grain	3/32in.(2.5mm)
Max.Air Consumption	20gpm(10L/s)
Air Inlet size	1/4in.npt(f)
Air Outlet size	3/8in.npt(f)
Fluid Inlet size	3/4 in.npt(f)or bspt(f)
Fluid Outlet size	3/4 in.npt(f)or bspt(f)
Weight	PVDF pump 3.7kg PP pump 2.8kg

Diagram



Installation





EMOCLEW AMERICA COMPANY LLC 7901 Kingspointe PKWY SUITE 28 - Orlando - FL - 32819 - USA +1 (407) 683-6437 emoclew@emoclewusa.com | info@emoclewpumps.com | www.emoclew.com