


MBV25 Aluminium Diaphragm Pump

Aluminium Diaphragm Pump



EMOCLEW AMERICA



Diaphragm Pump

MBV25 Aluminium Diaphragm Pump

Aluminium Diaphragm Pump



You can buy good quality MBV25 Aluminium Diaphragm Pump, we are the best distributor from USA market.

Description

Features

- 1 in (25.4 mm) center- and end-ported
- High flow – 40 gpm (151 lpm) in a compact, portable size
- Fluid pressure to 120 psi (8.4 bar, 0.84 MPa)
- Epoxy-coated center section for corrosive environments
- Equipped with an effective and reliable air valve system
- External controller for optional remote operation

Typical Applications

- Drum fluid transfer
- Unloading fluids

- Chemical evacuation
- Ceramic glaze supply
- Dewatering and sump evacuation
- Tank and sump drainage


Typical Fluids Handled

- Chemicals
- Contaminated surface water
- Adhesives, varnishes, dispersions, solvents and stains
- Resins, latexes, wood preservative stains, concrete paints and primers
- Ceramic slips and slurries


Parameter Table

MBV25 Aluminium Diaphragm Pump - Technical Specifications	
Max Working Pressure	120psi(0.84Mpa ,8.4bar)
Max Flow Rate	40 gpm(150 lpm)
Max Reciprocating Speed	276cpm
Max Suction Height(Dry Sucking)	5.48m
Max Permitted Grain	4mm
Max.Air Consumption	45scfm(22.5L/s)
Air Inlet size	1/2 in.npt(f)
Air Outlet size	1/2 in.npt(f)
Fluid Inlet size	1 in.npt
Fluid Outlet size	1 in.npt(f)
Weight	Aluminum pump 8.2kg Stainless steel 15kg

Diagram



Installation



EMOCLEW AMERICA COMPANY LLC

7901 Kingspointe PKWY SUITE 28 - Orlando - FL - 32819 - USA

+1 (407) 683-6437

emoclew@emoclewusa.com | info@emoclewpumps.com | www.emoclew.com