MBV40 PP Plastic Center Block Pump

Plastic Center Block Pump





MBV40 PP Plastic Center Block Pump

Plastic Center Block Pump

You can buy good quality MBV40 PP Plastic Center Block Pump, we are the best distributor from USA market.



Description

Features

- 1-1/2 in (38.1 mm) end-porting
- High flow 100 gpm (378 lpm) in a compact, portable size
- Fluid pressure to 120 psi (8.4 bar, 0.84 MPa)
- Patented, high-reliability closed center air valve is online serviceable
- Lube-free operation
- Epoxy-coated air section
- External controller for optional remote operation

Typical Applications

- Tank transfer
- Tank stripping
- Chemical tank plating
- Transferring high temperature acids and gases


Typical Fluids Handled

- Chemicals
- Corrosive fluids
- Acids and gases: acetic, chromic, hydrochloric, hydrofluoric, sulfuric, nitric and phosphoric


Parameter Table

MBV40 PP Plastic Center Block Pump - Technical Specifications	
Max Working Pressure	120psi(0.84Mpa ,8.4bar)
Max Flow Rate	118 gpm(446 lpm)
Max Reciprocating Speed	200cpm
Max Suction Height (Dry Sucking)	5m
Max Permitted Grain	5mm
Max. Air Consumption	80scfm(40L/s)
Air Inlet size	1/2 in.npt(f)
Air Outlet size	1/2 in.npt(f)
Fluid Inlet size	11/2 in.npt(f)
Fluid Outlet size	11/2 in.npt(f)
Weight	PVDF pump 20.0kg PP pump 16.0kg

Diagram



Installation





7901 Kingspointe PKWY SUITE 28 - Orlando - FL - 32819 - USA +1 (407) 683-6437